

02 Series

Electrified Powerbolts

IPIXA Security 02 Series Electrified Powerbolts represents reliable and cost effective Access Control solution

02 series offers electrified locks which can withstand 4500 lbs of linear positive impact. The locks are equipped with sensors to remotely monitor the status of the door. These high security locks are suitable for framed glass doors, wooden doors, metal doors & fire doors. The minimum maintenance feature & 3 years limited warranty on all models enables this range to be ideal for commercial applications.



AEL0210

Product Specifications

Type	: Fail Safe
Holding Force	: 1000 lbs
Operating Voltage	: 12 VDC
Current Draw	: Start Current 1200 mA; Standby Current 150 mA
Door Status Monitoring	: Inbuilt Door Status Monitoring
Operating Temperature	: -10°C - + 55°C
Relock Delay Timer	: Time Delay Adjustments 0, 3, 6 Seconds
Face Plate Dimension	: 146 (L)x 24 (W) x 39 (H) mm
Strike Plate Dimension	: 146 (L) x 24 (W) x 25 (H) mm
Weight	: 900 mg
Suitable for	: Surface Mounting on Narrow Doors



Special Features

- Low Temperature Design
- Ultra-Low-Power Design
- Built-in MOV reverse current prevention.
- Auto-relock if no Action within 5 secs

Cycle Tested
500,000



IPIXA SECURITY LIMITED
Kemp House, 160 City Road,
London, EC1V 2NX,
United Kingdom
ipixa.co.uk